
# Low-floor Multiple Units (EMU & DEMU)



## **Modular concept**



# **Technical specifications**

	EMU	DEMU
Track gauge	1435 mm	1435 mm
Axle arrangement	Bo'2'2'2'Bo'	Bo'2'2'Bo'
Catenary supply voltage	25 kV, 50 Hz	-
Continuous power (on wheels)	2000 kW	-
Power of diesel motors	-	2 x 390 kW
Maximum speed	160 km/h	120 km/h
Overall length	75000 mm	58500 mm
Carbody widht	2885 mm	2885 mm
Height with the lowered pantograph	4280 mm	4280 mm
Number of entrance doors (each side)	4	4
Width of entrance doors	1300 mm	1300 mm
Floor height	600 mm	600 / 1200 mm
Total passenger capacity (Urban and Commuter Operations)	420 passangers (211 sitting places)	-
Total passenger capacity (Regional Operations)	505 passangers (135 sitting places)	323 passangers (160 sitting places)



## **Key features**

- Active and passive safety systems for passengers and operating personnel, compliant with the latest crashworthiness standards
- A fully integrated passenger area without partition walls or doors, allowing for a seamless travel experience
- Air suspension system; HVAC system; comfortable seating
- Wide entrance doors and platform-level floors for easy boarding
- Multi-purpose space for wheelchair users with a hydraulic lift for easier boarding and disembarking
















- Designated space for bicycles
- Ergonomically designed and air-conditioned drivers' cab
- Capable of multiple operations with up to three units
- High reliability with low operational and maintenance costs
- **GPS** positioning
- Vehicle data exchange









#### KONČAR **ELECTRIC VEHICLES**

KONČAR - Electric Vehicles Inc. for manufacturing Ul. Ante Babaje 1, 10090 Zagreb, Croatia phone: +385 1 3496 933 e-mail: info@koncar-kev.hr

www.koncar.hr/en/koncar-electric-vehicles

